



●
Clean/Overdrive

●
Mode

●
Overdrive 1/ Overdrive 2

●
Solo Boost

Quickrod, ProMod, Streetrod 4 Button Footswitch Operation

1. Clean/Overdrive Switch -- LED on indicates Clean Channel -- Led off indicates OD Channel
2. Mode Switch -- LED off indicates 2nd Gear -- Led on indicates the gear that the front panel mode switch is set to
3. Overdrive 1/ Overdrive 2 Switch -- LED on indicates OD2 gain boost -- LED off indicates OD1
4. Solo Boost Switch -- LED on indicates Solo Volume control activated -- OD2 also is activated

Footswitch connections -- Two 1/4" TRS plugs on a 25' cable with 5 pin DIN connector

Setting up the Amplifier:

After unpacking your new amp, Turn the amp around so the back faces you. Remove the four screws to remove the back cover of the amp. You will find the tubes packaged tightly on the left side of the Amp. Carefully remove the package and remove the tubes. You will have three preamp tubes and four power section tubes.

Power Section Tubes:

Un-box the Power section tubes. Keep the boxes! They are marked with tube ratings! You will see on the base of the tube there is a "key" guide to align the tube into the socket. Starting with the tube socket on the far right, Line up the key with the slot in the socket, From the top of the tube, firmly press the tube into the socket until the base of the tube is flush with the Socket. Insert these tubes into the tube sockets. The tubes are matched so you may install them in no particular order. After you install a tube carefully hold the tube spring retainer and stretch it over the top of the tube and center it. These are light metal and can bend. If you happen to bend them you can shape it to the tube while its installed. Reinstall the rear cover and get ready to fire this monster amplifier to life!

WARNING:

Please Check the Voltage selector on the back for proper Voltage selection! Please check the volume control levels on all channels before powering on. After you plug in the amplifier, Flip the power switch down to turn on. Wait for a minute for the tubes to warm, then turn on the Standby switch. The Amp is ready for explosive guitar sounds!

This Amplifier will get VERY loud. Remember you only have one set of ears!

Dimensions

29" Wide, 11.5" Tall, 8.5" Deep, 50lbs

Limited Lifetime Warranty.

New Amplifiers are lifetime warranted to the original purchaser against failure of materials and workmanship. No other warranty applies. Tubes, transformers and speakers are warranted for a period of ninety days. This warranty applies only if the amplifier has not been damaged by accident, misuse or as a result of repair or modification. Splawn reserves the right to make any design changes without notice or obligation to incorporate these changes in products previously purchased.

Splawn Amplification
115 South Gaston St.
Dallas, NC 28034